

DVR404TAB



Specifications:

MODEL	DVR404TAB
Video Format	NTSC/PAL
Video Compression	MJPEG
Internet Transmitting / Compression	MPEG4
Display Frame Rate	120/100fps
Recording Frame Rate (Auto balance)	60/50fps
Display Resolution	640x448/640x544
Recording Resolution	640x224/640x272
Display Division	Single/Sequence/Split(1/4)
Video Input	BNCx4
Video Output	Video outx2, S-Videox1, VGAx1
Audio In/Out	1/1
Alarm In/Out	4/1
Recording Mode	Continuous/ Schedule / Motion Detection /Sensor
Recording Quality	High/Normal/Low
Search Mode	Time/Event
HDD Storage	Removable HDDx1, Internal 3.5"HDDx1 (Optional-IDE to SATA bridge)
Backup Device	USB stick /DVD±RW/CD-RW(option)
Serial Connectors	USB 2.0x1, Mouse(Combo USB&PS/2 protocol)x1, RS485x1, IR receiverx1 (optional)
Network Connection	10/100 Ethernet(RJ-45)
Network Protocol	TCP/IP, Static IP, DHCP, PPPOE, DDNS(through Router)
Network Remote	Remote monitoring, recording, playback and PTZ(Available soon) by Client Program and IE browser.

Power Supply	Input:AC100~240V 50/60 Hz,Output:DC12V
	Slim model:3A(IDE)/4A(SATA)
	Removable drive model:4A(IDE)/5A(SATA)
Dimension(WxHxD)	290X52X220mm(Slim model)
	340X60X280mm(Removable drive model)
Weight	Slim model:1.8kg(W/O HDD)
	Removable drive model:3kg(W/O HDD)

The Intelligent Digital Surveillance Platform



S/W upgradable via USBpen drive.



Authentication Management



IE browser supported for remote monitoring/ recording/ playback/ PTZ control



IR extender supports(optional): IR extender is designed to extend the IR receiver.